

TY20 šroubovací panelový kabelový spojovací konektor, IP68

Kód produktu: AM3071
 EAN13: -
 HS kód: 85369010

Varianty produktu:

Počet pinů: 2-pin, 3-pin, 4-pin, 5-pin, 6-pin, 7-pin

Parametry produktu:

Materiál pouzdra: Plast
 Krytí: IP68
 Montáž: Šroubením

Popis výrobku:

Voděodolný dokovací konektor pro vodiče o průměru 6 - 11.5mm. Šroubovací provedení. Zlacené kontakty.

Krytí: IP68

Pracovní teplota: -20 - 110°C

Relativní vlhkost: 90% - 95%

Materiál: Polyamid

Balení obsahuje samce i samici



Typ: TY20	2-pin	3-pin	4-pin	5-pin
Průměr kontaktů	2.8mm	2.8mm	2.8mm	1.8mm
Max. proud	25A	25A	25A	10A
Max. napětí	380V	380V	380V	380V
Max. průřez kabelu	4mm ²	4mm ²	4mm ²	1.5mm ²



TY16	02	03	04	TY28	02	03	04
Pin plug insulator front view				Pin plug insulator front view			
Contact diameter (φMM)	02.8X2	01.8X3	01X3	Contact diameter (φMM)	03.6x2	03.6x3	03.6x4
Rated current (A)	16A	10A	5A	Rated current (A)	45A	45A	45A
Operating Voltage (AC.V)	380V	380V	250V	Operating Voltage (AC.V)	380V	380V	380V
Pressure resistance (AC.A)	1500V	1500V	1500V	Pressure resistance (AC.A)	1500V	1500V	1500V
Contact resistance mΩ	1	2	5	Contact resistance mΩ	0.5	0.5	0.5
Insulation resistance MQ	2000	2000	2000	Insulation resistance MQ	2000	2000	2000
Cable specifications (mm ² /AWG)	<4/12	<1.5/14	<0.75/18	Cable specifications (mm ² /AWG)	<6/10	<6/10	<6/10

TY20	02	03	04	05	06	07
Pin plug insulator front view						
Contact diameter (φMM)	02.8X2	02.8X3	02.8X4	01.8X5	01X6	01X7
Rated current (A)	25A	25A	25A	10A	5A	5A
Operating Voltage (AC.V)	380V	380V	380V	380V	250V	250V
Pressure resistance (AC.A)	1500V	1500V	1500V	1500V	1500V	1500V
Contact resistance mΩ	1	1	1	2	5	5
Insulation resistance MQ	2000	2000	2000	2000	2000	2000
Cable specifications (mm ² /AWG)	<4/12	<4/12	<4/12	<1.5/14	<0.75/18	<0.75/18