

Smršťovací spojka-dutinka, různé průměry

Kód produktu: AM0551

EAN13: -

HS kód: 85369010



Varianty produktu:

Průřez vodiče: 0,25-0,34 mm², 0,50-1,00 mm², 0,75-1,50 mm², 1,50-2,50 mm², 2,50-4,00 mm², 4,00-6,00 mm², 6,00-10,00 mm²

Parametry produktu:

Krytí: IP67


Průrazné napětí: 1000 V

Popis výrobku:

Smršťovací poměr: 2:1

Materiál: Nylon


Pájka: bezolovnatý cín



Barva	Modelové označení	Průřez vodiče	A (min.)	L (min.)	B (min.)	B + C (max.)	C (min.)
Bílá	SST-11	0.25-0.35mm ²	1.7mm	26mm	1.0mm	1.7mm	0.76mm
Červená	SST-21	0.50-1.00mm ²	2.7mm	40mm	1.4mm	2.7mm	1.2mm
Zelená	SST-51	0.75-1.50mm ²	3.5mm	40mm	1.5mm	3.5mm	1.3mm
Modrá	SST-31	1.50-2.50mm ²	4.5mm	40mm	2.3mm	4.5mm	2.0mm
Fialová	SST-61	2.50-4.00mm ²	5.5mm	40mm	2.5mm	5.5mm	2.2mm
Žlutá	SST-41	4.00-6.00mm ²	6.0mm	40mm	3.7mm	6.0mm	3.4mm
Oranžová	SST-71		7.3mm	30mm	3.8mm	7.3mm	3.4mm



Low Temperature Solder Sleeve:
 Minimum Shrink Temperature: 80°C
 Minimum Temperature for Solder to Melt: 138°C



- ① Strip wire insulation 1/3 inch on both wire ends. Twist the strands together.
- ② Apply heat while continuously rotating the wire to make the terminal evenly heated.



- ③ The tubing will shrink down. Solder will melt and flow through the stripped wires.
- NOTE: NO Crimping Needed!**