

# TY20 skrue-panelkabel-stik, IP68

## Produktkoder:

Produktkode: AM3071

EAN13: -

HS-kode: 85369010

## Produktparametre:

Materiale til huset: Plast

Dækning: IP68

Installation: Ved at skrue



## Produktvarianter:

Antal stifter: 2-pin, 3-pin, 4-pin, 5-pin, 6-pin, 7-pin

## Produktbeskrivelse:

Vandtæt docking-stik til ledninger med en diameter på 6 - 11,5 mm. Skrues på design. Guldbelagte kontakter.

IP68-beskyttelse.

Driftstemperatur: -20 - 110 °C

Relativ luftfugtighed: 90% - 95%

Materiale: Polyamid

Pakken indeholder en han og en hun

Type: TY20	2-pin	3-pin	4-pin	5-pin
Diameter af kontakter	2,8 mm	2,8 mm	2,8 mm	1,8mm
Max. strøm	25A	25A	25A	10A
Max. spænding	380V	380V	380V	380V
Max. kabeltværsnit	4mm <sup>2</sup>	4mm <sup>2</sup>	4mm <sup>2</sup>	1,5 mm <sup>2</sup>

# Galleri:



T100				T100			
02	03	04	05	02	03	04	05
Pin plug female front view				Pin plug female front view			
Connector diameter (mm)	02.843	03.813	04.783	Connector diameter (mm)	02.843	03.813	04.783
Pin plug length (mm)	30	30	30	Pin plug length (mm)	30	30	30
Operating voltage (VAC)	100	100	100	Operating voltage (VAC)	100	100	100
Insulation resistance (MΩ)	1000	1000	1000	Insulation resistance (MΩ)	1000	1000	1000
Current resistance (A)	1	1	1	Current resistance (A)	1	1	1
Insulation resistance (MΩ)	1000	1000	1000	Insulation resistance (MΩ)	1000	1000	1000
Cable qualification (m/1000)	01.014	01.014	01.014	Cable qualification (m/1000)	01.014	01.014	01.014

  

T100				T100			
02	03	04	05	02	03	04	05
Pin plug female front view				Pin plug female front view			
Connector diameter (mm)	02.843	03.813	04.783	Connector diameter (mm)	02.843	03.813	04.783
Pin plug length (mm)	30	30	30	Pin plug length (mm)	30	30	30
Operating voltage (VAC)	100	100	100	Operating voltage (VAC)	100	100	100
Insulation resistance (MΩ)	1000	1000	1000	Insulation resistance (MΩ)	1000	1000	1000
Current resistance (A)	1	1	1	Current resistance (A)	1	1	1
Insulation resistance (MΩ)	1000	1000	1000	Insulation resistance (MΩ)	1000	1000	1000
Cable qualification (m/1000)	01.014	01.014	01.014	Cable qualification (m/1000)	01.014	01.014	01.014