

# Termisk sikring lodning RY Tf 250V 15A

Produktkode: AM7910

EAN13: -

HS-kode: 85361000



## Produktvarianter:

Aktionstemperatur: 155°C, 95°C, 100°C, 75°C, 113°C, 133°C,  
115°C, 73°C, 120°C, 130°C, 150°C, 80°C, 152°C, 121°C, 140°C,  
110°C, 157°C, 145°C, 105°C, 125°C, 142°C, 240°C, 205°C, 200°C,  
135°C, 280°C, 195°C, 216°C, 185°C, 192°C, 165°C, 250°C, 175°C,  
210°C, 167°C, 172°C, 255°C

## Produktparametere:

Nuværende: 15A

Spænding: 250V AC

Sikringstype: Hurtig

Materiale til huset: Aluminium

Version: Aksial


## Produktbeskrivelse:

Termisk sikring lodning

Nominel spænding 250V AC


Maks. spidsstrøm: 15 A

Størrelse: 4.2x12mm



Note: The dimensions for long lead devices are in parentheses.

#### Before action



At normal operating temperatures, the current is routed from one end through the metal casing, the contact, to the other end of the lead (contact line), making the circuit unblocked (and vice versa).

#### After action



When the device is in normal working condition, the temperature sensor is melted due to the temperature rise, and the temperature sensor is melted, the spring is automatically relaxed, and the contact piece moves under the action of the straight spring, causing the contact piece and the contact line. Disconnected, the circuit is cut off.