

Termisk sikring lodning RY Tf 250V 15A

Produktkoder:

Produktkode: AM6313

EAN13: -

HS-kode: 85361000

Produktparametre:

Nuværende: 15 A

Spænding: 250 V AC

Sikringstype: Hurtig

Materiale til huset: Aluminium

Version: Aksial



Produktvarianter:

Aktionstemperatur: 73 °C, 75 °C, 80 °C,
95 °C, 100 °C, 105 °C, 113 °C, 110 °C,
115 °C, 120 °C, 121 °C, 125 °C, 130 °C,
133 °C, 135 °C, 140 °C, 142 °C, 145 °C,
150 °C, 152 °C, 155 °C, 157 °C, 165 °C,
167 °C, 172 °C, 175 °C, 185 °C, 192 °C,
195 °C, 200 °C, 205 °C, 210 °C, 216 °C,
240 °C, 250 °C, 255 °C, 280 °C

Produktbeskrivelse:

Termisk sikring lodning

Nominal spænding 250V AC


Maks. spidsstrøm: 15 A

Størrelse: 4.2x12mm

Galleri:



Before action



At normal operating temperatures, the current is routed from one end through the metal casing, the contact, to the other end of the lead (contact lead), making the circuit unblocked (and vice versa).

After action



When the device is in normal working condition, the temperature sensor is melted due to the temperature rise, and the temperature sensor is melted, the spring is automatically released, and the contact piece moves under the action of the spring, causing the contact piece and the contact line. Disconnected, the circuit is cut off.

