

Industriesteckverbinder LP-16, Stecker auf Buchse (Vierkantbuchse)

Produktcodes:

Artikel-Nr.: AM8116

EAN13: -

HS kód: 85369010



Produktparameter:

Abdeckung: IP67

Produktvarianten:

Anzahl der Stifte: 2-pin, 3-pin, 4-pin,
5-pin, 7-pin, 8-pin, 9-pin

Beschreibung des Produkts:

Hochwertiger Industriesteckverbindersatz mit vergoldeten Kontakten.
Erhöhte Vibrationsfestigkeit.

Schutzart: IP67

Maximale Spannung: 500V (2/3/4-polig), 250V (5/7/8/9-polig)


Maximale temporäre Spannung: 2500V (2/3/4-polig), 1500V (5/7/8/9-polig)

Maximaler Strom: 10A (2/3/4-polig), 5A (5/7/8/9-polig)

Für Leiterdurchmesser: 3-7 mm

Isolationswiderstand:

Galerie:



LP-16 Datasheet

The number of pins	2Pins	3Pins	4Pins	5Pins	6Pins	7Pins	8Pins	9Pins	10Pins
Pin layout									
Rated current	5A	5A	5A	5A	5A	5A	5A	5A	5A
Operating voltage	60VDC	60VDC	60VDC	60VDC	60VDC	60VDC	60VDC	60VDC	60VDC
Withstanding voltage	200VDC	200VDC	200VDC	200VDC	200VDC	200VDC	200VDC	200VDC	200VDC
Conductance	100 A/2.5 / 1.50 A/2.5	100 A/2.5 / 1.50 A/2.5	100 A/2.5 / 1.50 A/2.5	100 A/2.5 / 1.50 A/2.5	100 A/2.5 / 1.50 A/2.5	100 A/2.5 / 1.50 A/2.5	100 A/2.5 / 1.50 A/2.5	100 A/2.5 / 1.50 A/2.5	100 A/2.5 / 1.50 A/2.5
Dimensions	Ø1.02 / Ø1.02	Ø1.02 / Ø1.02	Ø1.02 / Ø1.02	Ø1.02 / Ø1.02	Ø1.02 / Ø1.02	Ø1.02 / Ø1.02	Ø1.02 / Ø1.02	Ø1.02 / Ø1.02	Ø1.02 / Ø1.02
Weight	1.20g Max.	1.60g Max.	2.00g Max.	2.40g Max.	2.80g Max.	3.20g Max.	3.60g Max.	4.00g Max.	4.40g Max.
Quantity	1000 pieces	1000 pieces	1000 pieces	1000 pieces	1000 pieces	1000 pieces	1000 pieces	1000 pieces	1000 pieces
Storage temperature	-40°C ~ 100°C	-40°C ~ 100°C	-40°C ~ 100°C	-40°C ~ 100°C	-40°C ~ 100°C	-40°C ~ 100°C	-40°C ~ 100°C	-40°C ~ 100°C	-40°C ~ 100°C
Material	High performance engineering plastic	High performance engineering plastic	High performance engineering plastic	High performance engineering plastic	High performance engineering plastic	High performance engineering plastic	High performance engineering plastic	High performance engineering plastic	High performance engineering plastic
Insulation resistance	>1000 MΩ	>1000 MΩ	>1000 MΩ	>1000 MΩ	>1000 MΩ	>1000 MΩ	>1000 MΩ	>1000 MΩ	>1000 MΩ
Color	Black	Black	Black	Black	Black	Black	Black	Black	Black
Ordering code	AMPUL LP-16-02	AMPUL LP-16-03	AMPUL LP-16-04	AMPUL LP-16-05	AMPUL LP-16-06	AMPUL LP-16-07	AMPUL LP-16-08	AMPUL LP-16-09	AMPUL LP-16-10
Application	Automotive (ISO 16750-4) and other applications	Automotive (ISO 16750-4) and other applications	Automotive (ISO 16750-4) and other applications	Automotive (ISO 16750-4) and other applications	Automotive (ISO 16750-4) and other applications	Automotive (ISO 16750-4) and other applications	Automotive (ISO 16750-4) and other applications	Automotive (ISO 16750-4) and other applications	Automotive (ISO 16750-4) and other applications
Environmental conditions	Complies with RoHS and REACH standards	Complies with RoHS and REACH standards	Complies with RoHS and REACH standards	Complies with RoHS and REACH standards	Complies with RoHS and REACH standards	Complies with RoHS and REACH standards	Complies with RoHS and REACH standards	Complies with RoHS and REACH standards	Complies with RoHS and REACH standards
MATERIALS									
High performance plastic	High performance engineering plastic								
Insulation	2000V (1000V) high voltage								
Color	Black (RAL 9005)								
Material of cover	Steel (galvanized)								
Environmental conditions	Complies with RoHS and REACH standards								