



onswi dersta nd Max. L eiterq uersch nitt	mΩ	mΩ	mΩ	mΩ	mΩ	mΩ	mΩ	mΩ	mΩ	mΩ	mΩ
	≤6,15	≤6,15	≤6,15	≤6,15	≤2,54	≤2,54	≤0,78	≤0,78	≤0,78	≤0,78	≤0,78
	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>

Maximaler Strom: 25A

Maximale Spannung: 250 V AC

Schutzart: IP68

Arbeitstemperatur: -20 - 110°C

Relative Luftfeuchtigkeit: 90% - 95%

Material: Polyamid

Packungsinhalt: männlich + weiblich SP20

## Galerie:



Max. current: 25A  
 Max. voltage: 250V AC  
 Material: Polyamide  
 Protection: IP68  
 Temperature range: -20°C to 110°C  
 Dimensions: 66 x 20 x 22 mm  
 Weight: 10g  
 Reference: SP20