

Thermostat KSD9700 250V/16A, NC



Product codes:

Reference: AM3360

EAN13: -

UPC: 90321020

Product features:

Current: Max. 16 A

Voltage: 250 V AC

Contact: NC (Normally Closed)

Waterproof grade: IP65

Product attributes:

Action temperature: 50 °C, 55 °C, 60 °C,
65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C,
95 °C, 100 °C, 105 °C, 110 °C, 115 °C,
120 °C, 125 °C, 130 °C, 135 °C, 140 °C,
150 °C

Product description:

Fully encapsulated thermostat in industrial quality. Opens when the prescribed temperature is reached. At lower temperatures the thermostat is closed.

Applicable to all types of household appliances and electronic products. For example, electric motors, fluorescent lamps, battery chargers, transformers, solenoids, heating mats, etc..

NC (normal closed) circuit
working voltage 250V AC
max. current 16A

metal housing

size 21.5x8.4x3.8 mm

cable length 70 mm

price for 1 piece

Operating temperature	Resetting temperature	Operating temperature	Resetting temperature
25±5°C	≥15°C	105±5°C	75±15°C
30±5°C	≥20°C	110±5°C	75±15°C
35±5°C	≥25°C	115±5°C	80±15°C
40±5°C	≥30°C	120±5°C	85±15°C
45±5°C	≥33°C	125±5°C	85±15°C
50±5°C	≥35°C	130±5°C	90±15°C
55±5°C	42±6°C	135±5°C	95±15°C
60±5°C	48±10°C	140±5°C	100±15°C
65±5°C	48±10°C	145±5°C	100±15°C
70±5°C	50±12°C	150±5°C	105±15°C
75±5°C	53±14°C	155±5°C	110±15°C
80±5°C	55±15°C	160±5°C	115±15°C
85±5°C	60±15°C	165±5°C	115±15°C
90±5°C	65±15°C	170±5°C	120±15°C
95±5°C	70±15°C	175±5°C	125±15°C
100±5°C	70±15°C	180±5°C	130±15°C

Product gallery:

