

Thermostat KSD9700 250V/16A, NC

Reference: AM3360
EAN13: -
HS code: 90321020



Product attributes:

Action temperature: 50 °C, 55 °C, 60 °C, 65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 95 °C, 100 °C, 105 °C, 110 °C, 115 °C, 120 °C, 125 °C, 130 °C, 135 °C, 140 °C, 150 °C

Product features:

Current: Max. 16 A
Voltage: 250 V AC
Contact: NC (Normally Closed)
Waterproof grade: IP65

Product description:

Fully encapsulated thermostat in industrial quality. Opens when the prescribed temperature is reached. At lower temperatures the thermostat is closed.

Applicable to all types of household appliances and electronic products. For example, electric motors, fluorescent lamps, battery chargers, transformers, solenoids, heating mats, etc..

NC (normal closed) circuit
working voltage 250V AC
max. current 16A

metal housing

size 21.5x8.4x3.8 mm

cable length 70 mm
price for 1 piece

| Operating temperature | Resetting temperature | Operating temperature | Resetting temperature |
|-----------------------|-----------------------|-----------------------|-----------------------|
| 25±5°C | ≥15°C | 105±5°C | 75±15°C |
| 30±5°C | ≥20°C | 110±5°C | 75±15°C |
| 35±5°C | ≥25°C | 115±5°C | 80±15°C |
| 40±5°C | ≥30°C | 120±5°C | 85±15°C |
| 45±5°C | ≥33°C | 125±5°C | 85±15°C |
| 50±5°C | ≥35°C | 130±5°C | 90±15°C |
| 55±5°C | 42±6°C | 135±5°C | 95±15°C |
| 60±5°C | 48±10°C | 140±5°C | 100±15°C |
| 65±5°C | 48±10°C | 145±5°C | 100±15°C |
| 70±5°C | 50±12°C | 150±5°C | 105±15°C |
| 75±5°C | 53±14°C | 155±5°C | 110±15°C |
| 80±5°C | 55±15°C | 160±5°C | 115±15°C |
| 85±5°C | 60±15°C | 165±5°C | 115±15°C |
| 90±5°C | 65±15°C | 170±5°C | 120±15°C |
| 95±5°C | 70±15°C | 175±5°C | 125±15°C |
| 100±5°C | 70±15°C | 180±5°C | 130±15°C |

