

Resistor 1W, 1%, wired

Reference: AM2305

EAN13: -

UPC: 85332900

Product attributes:

Resistance: 1 mOhm, 1M0, 910 kOhm, 910K, 820 kOhm, 820K, 680 kOhm, 680K, 620 kOhm, 620K, 560 kOhm, 560K, 510 kOhm, 510K, 470 kOhm, 470K, 430 kOhm, 430K, 390 kOhm, 390K, 360 kOhm, 360K, 330 kOhm, 330K, 300 kOhm, 300K, 270 kOhm, 270K, 240 kOhm, 240K, 220 kOhm, 220K, 200 kOhm, 200K, 180 kOhm, 180K, 150 kOhm, 150K, 120 kOhm, 120K, 100 kOhm, 100K, 91 kOhm, 91K, 68 kOhm, 68K, 51 kOhm, 51K, 56 kOhm, 56K, 47 kOhm, 47K, 43 kOhm, 43K, 39 kOhm, 39K, 36 kOhm, 36K, 33 kOhm, 33K, 30 kOhm, 30K, 27 kOhm, 27K, 24 kOhm, 24K, 22 kOhm, 22K, 20 kOhm, 20K, 18 kOhm, 18K, 15 kOhm, 15K, 12 kOhm, 12K, 10 kOhm, 10K, 9.1 kOhm, 9K1, 8.2 kOhm, 8K2, 7.5 kOhm, 7K5, 6.8 kOhm, 6K8, 6.2 kOhm, 6K2, 5.6 kOhm, 5K6, 5.1 kOhm, 5K1, 4.7 kOhm, 4K7, 4.3 kOhm, 4K3, 3.9 kOhm, 3K9, 3.6 kOhm, 3K6, 3.3 kOhm, 3K3, 3 kOhm, 3K0, 2.7 kOhm, 2K7, 2.4 kOhm, 2K4, 2.2 kOhm, 2K2, 2 kOhm, 2K0, 1.8 kOhm, 1K8, 1.5 kOhm, 1K5, 1.2 kOhm, 1K2, 1 kOhm, 1K0, 910 Ohm, 910R, 750 Ohm, 750R, 820 Ohm, 820R, 680 Ohm, 680R, 620 Ohm, 620R, 560 Ohm, 560R, 510 Ohm, 510R, 470 Ohm, 470R, 430 Ohm, 430R, 390 Ohm, 390R, 360 Ohm, 360R, 330 Ohm, 330R, 300 Ohm, 300R, 270 Ohm, 270R, 240 Ohm, 240R, 220 Ohm, 220R, 200 Ohm, 200R, 180 Ohm, 180R, 150 Ohm, 150R, 120 Ohm, 120R, 100 Ohm, 100R, 91 Ohm, 91R, 82 Ohm, 82R, 75 Ohm, 75R, 68 Ohm, 68R, 62 Ohm, 62R, 56 Ohm, 56R, 51 Ohm, 51R, 47 Ohm, 47R, 43 Ohm, 43R, 39 Ohm, 39R, 36 Ohm, 36R, 33 Ohm, 33R, 30 Ohm, 30R, 27 Ohm, 27R, 62 kOhm, 62K, 75 kOhm, 75K, 82 kOhm, 82K, 22 Ohm, 22R, 20 Ohm, 20R, 18 Ohm, 18R, 15 Ohm, 15R, 12 Ohm, 12R, 10 Ohm, 10R, 8.2 Ohm, 8R2, 7.5 Ohm, 7R5, 6.8 Ohm, 6R8, 6.2 Ohm, 6R2, 5.1 Ohm, 5R1, 4.7 Ohm, 4R7, 3.9 Ohm, 3R9, 3.3 Ohm, 3R3, 2.7 Ohm, 2R7, 2.2 Ohm, 2R2, 1.5 Ohm, 1R5, 1 Ohm, 1R0, 2 Ohm, 2R0, 0.33 Ohm, R33, 0.5 Ohm, R50, 0.1 Ohm, R10, 5.6 Ohm, 5R6, 2.2 mOhm, 2M2



Product features:

Power P: 1W

Temperature coefficient: $\pm 50\text{ppm}/^\circ\text{C}$

Tolerance: 1%

Execution: Axial

Product description:

Metallized resistor, parameters can be found in the product specification.

I ($\pm 1\text{mm}$) d ($\pm 0.5\text{mm}$) and ($\pm 3\text{mm}$) yes ($\pm 0.05\text{mm}$) max. voltage 1W 11 mm 5 mm 28 mm 0.8mm 250V

