

Metal cable gland IP68, M

Reference: AM7953

EAN13: -

HS code: 85444290

Product attributes:

Thread: M8x1.0, M8x1.25, M10x1, M10x1.5, M12, M14, M16, M18, M20, M22, M24, M25 S, M25 B, M27, M30, M32, M33, M36, M40 S, M40 B, M42, M48, M50, M60



Product features:

Waterproof grade: IP68

Operating temperature: -40°C - +100 °C

Product description:

The cable glands are fully sealed and IP68 rated. This means that the metal glands are dust-tight and protected against the continuous effects of immersion in water. CGM-M cable glands are ideal for harsher environments and outdoor applications.

Excellent water resistance
Fully sealed against dust
High quality brass with nickel plating
NBR and polyamide retaining ring
For use with unarmored cable

Material: brass
Surface finish: chrome nickel

Thread	Cable diameter (mm)	Thread diameter	Mounting hole	Thread length	Hexagon size (key)
M8*1.0	3-3.8	7.7	8	5.5	14
M8*1.25	3-3.8	7.7	8	5.5	14
M10*1.5	3-6.5	9.7	10	6.5	14
M12*1.5	3-6.5	11.7	12	6	14
M14*1.5	4-8	13.7	14	6	16
M16*1.5	4-8	15.7	16	7	18
M18*1.5	6-10	17.7	18	7	20
M20*1.5	6-12	19.7	20	8	22
M22*1.5	10-14	21.7	22	8	24
M24*1.5	10-14	23.7	24	8	27
M25*1.5-S	10-14	24.7	25	9	27
M25*1.5-B	8-16	24.7	25	9	27
M27*1.5	13-18	26.7	27	9	30
M28*1.5	13-18	27.7	28	9	30
M30*1.5	13-18	29.7	30	9	32
M32*1.5	15-22	31.7	32	9	34
M33*1.5	15-22	32.7	33	10	36
M36*1.5	18-25	35.7	36	10	40
M37*1.5	18-25	36.7	37	10	40
M40*1.5	18-25	39.7	40	11	40/45
M40*1.5	22-28	39.7	40	11	45
M42*1.5	22-28	41.7	42	11	45
M47*1.5	25-32	46.7	47	11	50
M48*1.5	25-32	47.7	48	11	52
M50*1.5	32-38	49.7	50	11	55
M54*1.5	32-38	53.7	54	12	58

M60*1.5	37-44	59.7	60	12	64
M63*1.5	37-44	62.7	63	12	68
M64*1.5	37-44	63.7	64	12	68
M72*1.5	42-52	71.7	72	15	78
M75*1.5	42-52	74.7	75	15	78
M80*1.5	55-60	79.7	80	17	88
M88*1.5	65-70	87.7	88	18	98
M100*1.5	75-84	99.7	100	22	110

