

# Thermal fuse soldering RY Tf 250V 15A

## Product codes:

Reference: AM6313

EAN13: -

UPC: 85361000

## Product features:

Current: 15 A

Voltage: 250 V AC

Fuse type: Fast

Housing material: Aluminium

Execution: Axial



## Product attributes:

Action temperature: 73 °C, 75 °C, 80 °C,  
95 °C, 100 °C, 105 °C, 113 °C, 110 °C,  
115 °C, 120 °C, 121 °C, 125 °C, 130 °C,  
133 °C, 135 °C, 140 °C, 142 °C, 145 °C,  
150 °C, 152 °C, 155 °C, 157 °C, 165 °C,  
167 °C, 172 °C, 175 °C, 185 °C, 192 °C,  
195 °C, 200 °C, 205 °C, 210 °C, 216 °C,  
240 °C, 250 °C, 255 °C, 280 °C

## Product description:

Thermal fuse soldering

Rated voltage 250V AC

Max. peak current: 15 A


Size: 4.2x12mm

## Product gallery:

---



**Before action**



At normal operating temperatures, the current is routed from one end through the metal casing, the contact, to the other end of the lead (contact lead), making the circuit unblocked (and vice versa).

**After action**



When the device is in normal working condition, the temperature sensor is melted due to the temperature rise, and the temperature sensor is melted, the spring is automatically released, and the contact piece moves under the action of the spring, causing the contact piece and the contact line. Disconnected, the circuit is cut off.

