

SP2110/SP2112 panel mount, IP68 waterproof cable connector

Reference: AM1179
EAN13: -
HS code: 85369010



Product attributes:

Number of pins: 2-pin, 3-pin, 4-pin, 5-pin, 7-pin, 9-pin, 12-pin

Product features:

Housing material: Plastic
Waterproof grade: IP68
Construction: By soldering

Product description:

Waterproof docking connector for wires with a diameter of 6 - 12mm. Gold-plated contacts.

Type: SP2110 /SP2112	2-pin	3-pin	4-pin	5-pin	5C-pin	7-pin	9-pin	12-pin
Rated current	30A	30A	30A	30A	15A	15A	5A	5A
Contact diameter	3mm	3mm	3mm	3mm	2mm	2mm	1mm	1mm
Maximum voltage	500v	500v	500v	500v	500v	500v	500v	400v
Contact resistance MΩ	1	1	1	1	2.5	2.5	5	5
Wire cross-section mm ² /AWG	≤4.17/11	≤4.17/11	≤4.17/11	≤4.17/11	≤2/14	≤2/14	≤0.785/18	≤0.785/18

Protection: IP68

Working temperature: -35 - 110°C

Relative humidity: 90% - 95%

Material: Polyamide

Package contents: 1x panel socket (female), 1x cable connector (male)



