

# SP1710/SP1712 panel mount, IP68 waterproof cable connector

Reference: AM7411  
EAN13: -  
HS code: 85369010



## Product attributes:

Number of pins: 2-pin, 3-pin, 4-pin, 5-pin, 7-pin, 9-pin

## Product features:

Housing material: Plastic  
Waterproof grade: IP68  
Construction: By soldering

## Product description:

Waterproof docking connector for wires with a diameter of 5 - 10mm. Gold-plated contacts.

Type:	2-pin	3-pin	4-pin	5-pin	7-pin	9-pin
SP1710/SP1712						
Contact diameter	1.5mm	1.5mm	1mm	1mm	1mm	1mm
Maximum current	10A	10A	10A	10A	10A	10A
Maximum voltage	500V	500V	500V	500V	400V	400V
Contact resistance	2.5mΩ	2.5mΩ	5mΩ	5mΩ	5mΩ	5mΩ
Max. conductor cross-section	2mm <sup>2</sup>	2mm <sup>2</sup>	0.785mm <sup>2</sup>	0.785mm <sup>2</sup>	0.785mm <sup>2</sup>	0.785mm <sup>2</sup>

Protection: IP68

Working temperature: -35 - 110°C

Relative humidity: 90% - 95%

Material: Polyamide

Package contents: 1x panel socket (female), 1x cable connector (male)

