SP13 panel mount, IP68 waterproof cable connector

Reference: AM7967
EAN13: -
HS code: 85369010

Product attributes:

Number of pins: 1-pin, 2-pin, 3-pin, 4-pin, 5-pin, 6-pin, 7-pin

Product features:

Voltage: 250 V AC
Housing material: Plastic

Product description:

Waterproof panel connector for conductors with a diameter of 4 - 6.5mm. Gold plated contacts.

Type: SP13	1-pin	2-pin	3-pin	4-pin	5-pin	6-pin	7-pin
Diameter of contacts	2.8mm	1.8mm	1mm	1mm	1mm	1mm	1mm
Maximum current	10A	10A	5A	5A	5A	5A	5A
Maximum voltage	250V	250V	250V	250V	250V	250V	250V
Contact resistance	2mΩ	2mΩ	5mΩ	5mΩ	5mΩ	5mΩ	5mΩ
Max. conductor cross-section	$6.15mm^2$	$2.54mm^2$	$2mm^2$	$0.785mm^2$	$0.785mm^2$	$0.785mm^2$	$0.785mm^2$

Protection: IP68

Operating temperature: -20 - 110°C

Relative humidity: 90% - 95%

Material: Polyamide

Ø12.5

14.3

Ø20

2

Ø12

22

Ø6,5 (PG7)

52