

# Voltage converter 5-30V to 0.5-30V DC, max. 4A (SK35)

Reference: AM2404  
EAN13: -  
HS code: 85044090

## Product attributes:

## Product features:

Input voltage: 5-30 V DC  
Output voltage: 0.6-30 V DC  
Output power: 50 W  
Waterproof grade: IP20  
Max. current: 4 A

## Product description:

This DC/DC converter is used to regulate the input voltage, which has an input voltage range from 5 to 30V. The output voltage ranges from 0.6 to 30 V. The value of the output voltage can be adjusted using a rotary switch. The module includes short-circuit protection, temperature fuse (100°C).

Input voltage: 5-30V

Output voltage: 0.6-30V DC

Max. current: 4A

Max. power: 35W with cooling up to 50W

Output short circuit protection

Operating temperature: -40 to 85°C

Dimensions: 79x43x36mm

Mounting hole: 76x40mm

Weight: 95g

Model: SK35



This DC/DC converter is used to regulate the input voltage, which has an input voltage range from 5 to 30V. The output voltage ranges from 0.6 to 30 V. The value of the output voltage can be adjusted using a rotary switch. The module includes short-circuit protection, temperature fuse (100°C).

Input voltage: 5-30V

Output voltage: 0.6-30V DC

Max. current: 4A

Max. power: 35W with cooling up to 50W

Output short circuit protection

Operating temperature: -40 to 85°C

Dimensions: 79x43x36mm

Mounting hole: 76x40mm

Weight: 95g

Model: SK35

**NOTE: For loads above 35W, the module needs to be cooled with a fan.**



