

Time switching module, 220-240V AC

Reference: AM4329

EAN13: -

UPC: 85364190

Product attributes:

Product features:

Voltage: 220-240V AC
Waterproof grade: IP20
Max. current: 10A



Product description:

Panel module for timing, delay, cycling, intermittent timing and more.

Operating Voltage: 220-240V Switching

Voltage: max 30V DC (5A) 240V AC (5A)

Operating Temperature: -40 to 85°C Dimensions

: 79x43x26mm Mounting

Hole: 73x40mm Weight

: 55g

Instruction Manual:

Short press the RESTART button to turn the timer on, long press to turn it off. By short pressing the SET button, the desired temperature can be set with the up and down arrows when the display flashes. By long pressing the SET button followed by the arrow keys, the other functions of the thermostat can be set:

1. Long press SET to set the module. Then short to set P0 or P1.

P0--0 - Timing in seconds
P0--1- Timing in minutes
P0--2- Timing in hours
P1--0- After T1, on
P1--1- After T1, off
P1--2- After T1, on, after T2, off, end
P1--3- After T1 expiration, trip, after T2 expiration, trip, end
P1--4- After T1 expiration, trip, after T2 expiration, cycling
P1--5- After T1 expiration, trip, after T2 expiration, cycling

2. Press SET to set T1 (red display), use the arrow keys to set the desired value. After setting the value, you must wait 6 seconds for automatic saving

3. after setting the time T1 again briefly SET, green LED flashes, T2 set with arrow keys. Wait 6 seconds after setting the value.

The product is not a stand-alone functional unit, it requires professional assembly.

