

# Rocker switch KCD4 rectangular, ON-OFF-ON, momentary (non-latching), arrows, black, 250V/15A

## Product codes:

Reference: AM2740

EAN13: -

UPC: 85365080



## Product features:

Current: 15 A

Voltage: Max. 250 V

Color: Black

Connector: Faston 6.3 mm

Waterproof grade: IP20

Number of pins: 6-pin

## Product attributes:

## Product description:

Rectangular rocker switch type KCD4 is designed for panel mounting and switching circuits in three positions ON-OFF-ON. The design is non-latching (momentary), i.e. after release the lever returns to the initial position. Arrow pictograms o > facilitate operator orientation during directional control.

## Technical specifications

- Type: KCD4
  - Contact function: ON-OFF-ON (switch)
  - Version: without locking (torque)
  - Rated load: max. 250 V / 15 A
  - Rated load (alternative): 125 V / 20 A
  - Number of pins: 6-pin
  - Connectors: Faston 6.3 mm
  - Protection: IP20
-

- Color: black
- Markings on the cradle: arrows o >
- Mounting hole (cut-out): 29.5 x 22.4 mm
- Body dimensions: 31 x 25 x 35 mm
- Installation height (required depth in the panel): 28 mm

### **Functions and features**

- Three-position ON-OFF-ON switch for direction selection or two modes with neutral position
- Non-detenting torque design for short-term operation
- Panel mounting in a rectangular cutout
- Terminals for quick connection using 6.3 mm Faston flat connectors
- Pictograms on the cradle for clear position identification

### **Ideal for**

- Control panels and switchboards
- Directional control of DC motors (e.g. forward/reverse) in combination with appropriate wiring
- Device mode control with center off position
- Industrial and workshop applications, test fixtures

### **Package contents**

- 1x KCD4 rocker switch

### **Why choose this product?**

- Standard KCD4 format for easy replacement in existing panels
- Torque version suitable for control where return to the starting position is required
- Simple connection via 6.3 mm Faston and quick panel mounting
- Clearly defined mounting hole and installation depth for panel design

### **Installation and operating instructions**

- Before installation, verify the mounting hole size of 29.5 x 22.4 mm and the required depth in the panel of 28 mm.
- For connections, use the corresponding 6.3 mm Faston connectors and wires sized for the current load of the application.
- Verify the connection of the contacts by measurement or according to the diagram of your application (ON-OFF-ON, 6 pins).

### **Safety notice**

- When using the product on a mains voltage of 220–250 VAC, it is necessary to follow the principles of working on electrical equipment.
-

Carry out installation and service only when the power supply is disconnected.

- Observe the required insulation distances, fuses and enclosures according to the specific application. IP20 enclosure does not protect against water ingress.

## Product gallery:

