

XS6 mini metal panel connection connector, 90°

Reference: AM9458
EAN13: -
HS code: 85369010



Product attributes:

Number of pins: 2-pin, 3-pin, 4-pin, 5-pin

Product features:

Color: Silver
Waterproof grade: IP65
Mounting hole: 6 mm

Product description:

Waterproof docking connector for wires with a diameter of 4 mm. Bayonet design. Gold plated contacts. Suitable for sensors with DC voltage.

Mounting hole diameter: 6mm

Protection: IP65

Insulation resistance: 100 mΩ

Rated voltage: 30V DC, 0.2A

Working temperature: -25 - 85°C

Relative humidity: 90% - 95%

Material: Metal (brass with nickel plating)

The package contains both a male and a female

Weight: 10g

Type: XS6	2-pin	3-pin	4-pin	5-pin
Average contacts	1.6mm	1.6mm	1 mm	1 mm
Max. current	3.5A	3.5A	3.5A	3.5A
Max. Tension	30V	30V	30V	30V
Max. cable cross-section	0.6mm ²	0.6mm ²	0.6mm ²	0.6mm ²





XS8(2-5P)	
Operating temperature range	-20~101°C
Rated voltage	DC30V/0.2A
Insertion resistance	$\leq 0.01\Omega$
Current	3.5A
Insulation resistance	$\geq 100M\Omega$
Withstand voltage	AC250V(50Hz)1min
Insertion force	0.35N
Life	1000 times

