SP2110/SP2111, IP68 waterproof cable connector

Reference: AM8948
EAN13: -
HS code: 85369010

Product attributes:

Number of pins: 2-pin, 3-pin, 4-pin, 5-pin, 7-pin, 9-pin, 12-pin

Product features:

Housing material: Plastic
Waterproof grade: IP68
Construction: By soldering

Product description:

Waterproof docking connector for wires with a diameter of 6 - 12mm. Gold-plated contacts.

Type: SP2110/SP2112	2-pin	3-pin	4-pin	5-pin	7-pin	9-pin	12-pin
Contact diameter	3mm	3mm	3mm	3mm	2mm	1mm	1mm
Maximum current	30A	30A	30A	30A	15A	5A	5A
Maximum voltage	500V	500V	500V	500V	500V	500V	400V
Contact resistance	1mΩ	1mΩ	1mΩ	1mΩ	2.5mΩ	5mΩ	5mΩ
Max. conductor cross-section	$4.17mm^2$	$4.17mm^2$	$4.17mm^2$	$4.17mm^2$	$2mm^2$	$0.785mm^2$	$0.785mm^2$

Protection: IP68

Working temperature: -35 - 110°C

Relative humidity: 90% - 95%

Material: Polyamide

Package contents: 1x cable socket (female), 1x cable connector (male)