

# Voltage converter from 12V to 60V, 33.3A, 2000W, IP22

Reference: AM2450

EAN13: -

UPC: 85044090

## Product attributes:

## Product features:

Input voltage: 12V DC  
Output voltage: 60V DC  
Output current: 33.3A  
Output power: 2000W  
Waterproof grade: IP68  
Lifetime: 50,000 hours



## Product description:

Rack DC/DC voltage converter from 12V DC to 60V DC max. short-term 33.3A.

Input voltage: 12 V DC (10.5-16V DC)  
Output voltage: 560 V DC, max. 33.3A (short-term), continuous 26.6A  
Efficiency: 90%  
No-load consumption: max. 100mA  
Protection against overload, overvoltage, overheating, short circuit  
Aluminum construction with fins for heat dissipation  
Certificates: CE, ROHS  
Working temperature: -30 ~ +65 °C  
Ambient humidity: 20~90% RH  
Protection: IP68  
Size: 440x300x110mm  
Weight: 5500g

Mounting: 19" 2.5U Rack

The source is designed for continuous operation.

For loads with a relatively stable operating current, it is recommended to control the load rate of continuous operation at approximately 80%. Inductive, capacitive, power amplifiers, radios and other power motor class loads are better when the load is around 50%. This type of load has a large dynamic performance.

