

Buzzer for hole diameter 16mm, stainless steel

Reference: AM7014
EAN13: -
HS code: 85414100



Product attributes:

Tension: 12 V DC, 24 V DC

Product features:

Color: Silver
Waterproof grade: IP65
Mounting hole: 16 mm
Backlight: Red

Product description:

The metal buzzer with integrated LED indicator in the design for a 16 mm mounting hole is designed for acoustic and optical signaling in industrial switchboards, control panels and compact devices. Thanks to the stainless steel body and IP65 protection, it is also suitable for demanding environments with dust and moisture. The intermittent sound tone in combination with LED signaling provides a clear and immediate notification of the device status.

Technical specifications

- Operating voltage: 12 V DC, 24 V DC, 230 V AC (depending on the selected variant)
- Maximum current: 20 mA
- Buzzer volume (at a distance of 10 cm): 85 dB
- Tone frequency: 2500 Hz
- Audible signal: intermittent tone
- LED color: red
- Front diameter: 18 mm
- Total length: 35 mm
- Mounting hole diameter: 16 mm
- Thread: M16 × 1
- Weight: 42g
- Body material: stainless steel
- Protection: IP65
- Operating temperature: -25 °C to +80 °C
- Terminals: screw terminal block

Functions and features

- Combination of acoustic and optical signaling in one element
- All-metal design made of stainless steel with high mechanical resistance
- Intermittent audible tone for a clear warning signal
- LED indicator for clear visual status indication
- Sealed construction suitable for dusty and humid environments
- Compact dimensions suitable for panels with limited space
- Easy panel mounting using a Ø 16 mm hole

Ideal for

- Compact industrial control cabinets
- Machine control and signaling panels
- Warning and fault signaling
- Automation and control systems
- Applications requiring high protection IP65

Package contents

- Metal buzzer with LED indicator
- Mounting nuts for panel mounting
- Sealing element to ensure IP65 protection

Why choose this product?

- Durable stainless steel design with long service life
- Reliable combination of sound and light signaling
- High IP65 protection for demanding operating conditions
- Small mounting hole \varnothing 16 mm saves space in the panel
- Suitable for professional industrial use

