Power supply socket 54.6V, 2A, 5.5x2.1mm, lithium battery charger

Reference: AM3084

EAN13: -UPC: 85044090

Product attributes:

Product features:

Voltage: 54.6 V DC

Input voltage: 100-240 V AC, 50/60 Hz

Output current: 2 A Output power: 109 W Cable length: 120 cm Connector: 5.5x2.1 mm Waterproof grade: IP22



Product description:

The premium 54.6V lithium battery charger is the perfect choice for a wide range of electric vehicles such as wheelchairs, golf carts and electric scooters. Thanks to advanced technologies and intelligent charging, it ensures fast, efficient and safe charging of your batteries.

Main advantages:

- Fast charging: The fast charging function saves your time and allows you to resume operation as soon as possible.
- Intelligent charge indicator: Clearly displays the current charge status, so you always know when the battery is ready.
- Maximum Protection: The safety system includes over-voltage (OVP), over-current (OCP), over-load (OLP) and short-circuit (SCP) protection, ensuring long battery life and safety during charging.

This charger is the ideal choice for anyone looking for a reliable, fast and safe solution for recharging lead acid batteries. Thanks to its compact design and easy operation, it will become an indispensable helper for your electric vehicle.

Instructions and maintenance:

- 1. When charging the battery, first connect the charger to the battery, then to the mains. After charging, first disconnect the mains and then the charger from the battery. Improper disconnection may damage the battery.
- 2. Continue charging for 2-3 hours after the LED light turns green.
- 3. Charge in a dry environment.
- 4. If you are not using the charger, please disconnect it in time.
- 5. Charge the battery before it is completely discharged to avoid damaging it.

Parameters:

Input voltage: 100-240 V AC, 47-63 Hz.

Output voltage: 54.6V DC, 2A

Connector Size 5.5mm (outer diameter) x 2.1mm (inner diameter)

The positive pole is on the inner shell.

Package Contents:

- Battery charger
- User manual

