

Power Supply 36V, 41.7A - 1500W - 1 Output

Product codes:

Reference: AM8169

EAN13: -

UPC: 85044090

Product features:

Input voltage: 180-264 V AC, 45-65 Hz

Output voltage: 36 V DC

Output current: 41.7 A

Output power: 1500 W

Waterproof grade: IP20



Product attributes:

Product description:

Presenting the IPS-SP-1500 series of highly reliable industrial switching power supplies, designed for demanding applications requiring precisely regulated power. Each model offers smooth regulation of output voltage and current, allowing precise adaptation to your application requirements. These robust metal-encased supplies with IP20 protection are ideal for mounting into distribution cabinets and industrial systems.

Key Features:

- **Variable Output Voltage:** Smoothly adjustable from 0 V to 36 V DC using a precise adjustment trimmer
- **High Output Current:** Stable 41.7 A for demanding applications
- **Wide Input Voltage Range:** 180-264 V AC, 45-65 Hz
- **High Efficiency:** 87% for economical operation with minimal thermal losses
- **Active Cooling:** Ensures optimal operating temperature even under high load

Comprehensive Protective Functions:

- Overload Protection (105%–150%)
- Overvoltage Protection
- Short Circuit Protection with Automatic Recovery
- Thermal Protection at $\geq 70\text{ }^{\circ}\text{C}$ with Automatic Recovery below $50\text{ }^{\circ}\text{C}$

Practical Design:

- Standard Terminal Block with Screws for Easy Connection
- LED Indicator for Visual Power Check
- Durable Metal Construction Ensuring Long Life

Advanced Control Features:

- **External Potentiometer:** Option for Remote Voltage and Current Control
- **Analog Voltage Control:** Supports 0–5 V / 0–10 V Control Signal
- **Auxiliary Power Output:** 12 V 0.5 A for Powering External Devices
- **Remote Switching:** Default State On, Off by High Level (3 V–12 V)

Ideal Applications:

- **Automation Systems:** Control of Industrial Processes and Production Lines
- **Servo Drives and Motors:** Precise Power Control for Various Drives
- **Telecommunication Equipment:** Reliable Power Supply for Critical Communication Systems
- **Industrial Control Systems:** Stable Power Supply for PLCs and Other Control Elements
- **Testing and Measuring Equipment:** Precise Power Supply for Laboratory and Testing Applications
- **Entry Gates and Security Systems:** Uninterruptible Power Supply for Security Elements

Technical Specifications:

- **Input Voltage:** 180–264 V AC, 45–65 Hz
 - **Output Voltage:** 0–36 V DC
 - **Output Current:** max. 41.7 A (36 V DC)
 - **Output Voltage Accuracy:** $\pm 1.0\%$
 - **Line Regulation:** $\pm 1.0\%$
 - **Load Regulation:** $\pm 1.0\%$
 - **Efficiency:** 87%
 - **Start-Up Time:** 1500 ms, 100 ms at 230 V AC (full load)
 - **Output Voltage Ripple:** 200–1000 mV (depending on model)
 - **Insulation Resistance:** 100 M Ω at 500 V DC (25 $^{\circ}\text{C}$, 70% RH)
 - **Dielectric Strength:** I/P-O/P: 1.2 kV AC, I/P-FG: 1.2 kV AC, O/P-FG: 0.5 kV AC
-

- **Operating Temperature:** -20 °C to +60 °C
- **Operating Humidity:** 0-90% RH (non-condensing)
- **Vibration Resistance:** 10-500 Hz, 2 G (10 min/cycle tests, X, Y, Z axes for 60 min.)
- **Dimensions:** 277 × 155 × 70 mm (L × W × H)
- **Weight:** 2.4 kg

Product gallery:

