

LED metal indicator light with wires, for hole diameter 19mm, silver

Product codes:

Reference: AM0337

EAN13: -

UPC: 85414100



Product features:

Current: 20 mA

Color: Silver

Waterproof grade: IP65

Lifetime: 40,000 hours

Mounting hole: 16 mm

IC coverage: IK08

Product attributes:

Tension: 3-6 V DC, 12-24 V DC, 110-220 V AC

Backlight color: Red, Green, Blue, Yellow, White

Product description:

Professional metal LED indicator with a diameter of 19 mm is designed for reliable signaling of power, operation or equipment failure. Thanks to a wide voltage range and five available colors (yellow, blue, red, green, white), it is an ideal choice for industrial control panels, switchboards, measuring instruments and hobby projects.

Technical specifications

- **Model:** HYD-L-19
 - **Mounting hole diameter:** 19 mm
 - **Supply voltage:** 3-6V / 12-24V / 110-220V (depending on variant)
 - **Light source type:** LED
 - **Body material:** metal (aluminum alloy with chrome finish)
 - **LED colors:** yellow, blue, red, green, white
-

- **Luminosity:**
 - Red: 900–1200 mcd
 - Green: 1600–2200 mcd
 - Yellow: 1300–1800 mcd
 - Blue: 1000–1600 mcd
 - White: 2000–2500 mcd
- **Rated LED current:** 10–20 mA (depending on voltage version)
- **Protection level:** IP65
- **Mechanical resistance:** IK08
- **LED life:** up to 40,000 hours
- **Body dimensions:** 25 × 23 mm
- **Thread:** M19×1
- **Connection:** 150mm wires
- **Operating temperature:** -25°C to +80°C
- **Weight:** 21 g

Functions and features

- High brightness and long life of LED diodes
- Metal body with non-flammable base for safe operation
- Sealing ensures resistance to dust and moisture (IP65)
- Easy installation in a 19 mm diameter hole
- Suitable for direct connection to DC and AC voltage
- Different color variants for clear and concise signaling
- Elegant industrial design and quality workmanship

Ideal for

- Control and dashboards
- Electrical switchboards
- Industrial machines and CNC equipment
- Electronic devices and laboratory equipment
- DIY projects and modules for hobby electronics

Package contents

- 1× metal signal light HYD-L-19 (color according to the selected variant)
- 1× mounting nut
- 1× sealing ring (O-ring) for protection against moisture

Why choose this product?

- Extended mounting diameter of 19 mm for stable mounting
 - Universal power supply range 3–220 V AC/DC
 - High-quality metal construction with long service life
 - High luminosity and excellent visibility even in daylight
 - Safe and quick installation in panels or distribution boards
-

- Five colors available for different signaling purposes

Product gallery:

