

USB charger 45 W PD/QC, 1× USB-C + 1× USB-A, model RS-45PQ (black/white)

Reference: AM4704
EAN13: -
HS code: 85044090



Product attributes:

Color: White, Black

Product features:

Input voltage: 100-240 V AC, 50/60 Hz
Performance: 45 W

Product description:

Compact mains USB charger for powering and charging mobile phones, tablets and other devices via USB. It offers two outputs (USB-C and USB-A) and supports fast charging via USB-C Power Delivery and USB-A Quick Charge. Available in black or white.

Technical specifications

- Model: RS-45PQ
- Color: white / black
- Maximum power: 45W
- Input: 100-240V AC, 50/60Hz, 0.8A max.
- Outputs: 1× USB-C, 1× USB-A
- USB-C (PD): 5 V / 3 A, 9 V / 3 A, 12 V / 3.75 A, 15 V / 3 A, 20 V / 2.25 A (max. 45 W)
- USB-C (PPS): 3.3-11.0 V / 3.0 A, 3.3-16.0 V / 2.8 A
- USB-A: 5 V / 3 A, 9 V / 2 A, 12 V / 1.5 A (max. 18 W)
- Plug: EU / US / UK (depending on version)
- Dimensions: 47 × 40 × 61 mm
- Weight: 160g

Functions and features

- Fast charging support: USB Power Delivery (USB-C) and Quick Charge (USB-A)
- Two independent charging ports for connecting two devices simultaneously
- Protections: overcurrent, overvoltage, undervoltage, short circuit, overheating
- Shell material: PC with increased flame resistance

Ideal for

- Charge phones and tablets via USB-C or USB-A
- Devices requiring USB-C Power Delivery up to 45W
- Travel use thanks to wide input voltage range of 100-240 V AC

Package contents

- 1× RS-45PQ mains USB charger (black or white)

Why choose this product?

- Clearly defined output profiles for USB-C PD including PPS
- USB-C and USB-A combo for compatibility with a wide range of devices
- Integrated protection functions for stable operation and protection of connected devices

Installation and operating instructions

- Connect the charger to a power outlet that matches the plug used.
- For fast charging, use a quality cable designed for the required current and mode (PD/QC/PPS).
- When using both ports simultaneously, please note that the available power is divided between the connected devices.

Safety notice

- The device is intended for use in a 100-240 V AC electrical network. Improper handling may result in electric shock.
 - Do not use the charger if the cover or plug is damaged.
 - Ensure adequate ventilation, do not cover the charger during operation and do not expose it to moisture.
-

