

ión nominal	V	V	V	V	V	V	V	V	V	V	V	V	V	V	V
Resistencia de contacto	0,5 mΩ	0,5 mΩ	0,5 mΩ	1 mΩ	1 mΩ	1 mΩ	2 mΩ	2 mΩ	2 mΩ	2 mΩ	2 mΩ	5 mΩ	5 mΩ	5 mΩ	5 mΩ
Resistencia de aislamiento	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ	2000 mΩ
Sección transversal máxima del conductor	≤10,17 mm ²	≤10,17 mm ²	≤10,17 mm ²	≤6,15 mm ²	≤6,15 mm ²	≤6,15 mm ²	≤2,54 mm ²	≤2,54 mm ²	≤2,54 mm ²	≤2,54 mm ²	≤2,54 mm ²	≤0,78 mm ²	≤0,78 mm ²	≤0,78 mm ²	≤0,78 mm ²

Voltaje máximo: 250 V CA

Protección: IP68


Temperatura de trabajo: -20 - 110°C

Humedad relativa: 90% - 95%

Material: poliamida

Galerie:





022	3	4	5	6	7
Male contact					
Female					
Contact diameter	3.00	3.00	3.00	3.00	3.00
Rated current	10A	10A	10A	10A	10A
Rated voltage	250V	250V	250V	250V	250V
Test voltage (AC V)	500V	500V	500V	500V	500V
Rated voltage (DC V)	100V	100V	100V	100V	100V
Contact resistance (mΩ)	10	10	10	10	10
Insulation resistance (MΩ)	100	100	100	100	100
Operating temperature (°C)	-40	-40	-40	-40	-40

023	3	4	5	6	7
Male contact					
Female					
Contact diameter	3.00	3.00	3.00	3.00	3.00
Rated current	10A	10A	10A	10A	10A
Rated voltage	250V	250V	250V	250V	250V
Test voltage (AC V)	500V	500V	500V	500V	500V
Rated voltage (DC V)	100V	100V	100V	100V	100V
Contact resistance (mΩ)	10	10	10	10	10
Insulation resistance (MΩ)	100	100	100	100	100
Operating temperature (°C)	-40	-40	-40	-40	-40