

# Fusible térmico de soldadura RY Tf 250V 15A

## Códigos de producto:

Kód produktu: AM6313

EAN13: -

HS kód: 85361000

## Parámetros del producto:

Actual: 15 A

Tensión: 250 V AC

Tipo de fusible: Rápido

Material de la carcasa: Aluminio

Versión: Axial



## Variantes de productos:

Temperatura de acción: 73 °C, 75 °C, 80 °C, 95 °C, 100 °C, 105 °C, 113 °C, 110 °C, 115 °C, 120 °C, 121 °C, 125 °C, 130 °C, 133 °C, 135 °C, 140 °C, 142 °C, 145 °C, 150 °C, 152 °C, 155 °C, 157 °C, 165 °C, 167 °C, 172 °C, 175 °C, 185 °C, 192 °C, 195 °C, 200 °C, 205 °C, 210 °C, 216 °C, 240 °C, 250 °C, 255 °C, 280 °C

## Descripción del producto:

Soldadura de fusibles térmicos

Tensión nominal 250V AC

Corriente máxima de pico: 15 A


Tamaño: 4,2x12mm

## Galerie:

---



**Before action**



At normal operating temperatures, the current is routed from one end through the metal casing, the contact, to the other end of the lead (contact lead), making the circuit unblocked (and vice versa).

**After action**



When the device is in normal working condition, the temperature sensor is melted due to the temperature rise, and the temperature sensor is melted, the spring is automatically released, and the contact piece moves under the action of the spring, causing the contact piece and the contact line. Disconnected, the circuit is cut off.

