

LP-16 industrijski konektor, muški + ženski (četvrtasta utičnica)

Šifre proizvoda:

Šifra proizvoda: AM8116

EAN13: -

HS kód: 85369010



Parametri proizvoda:

Pokriti: IP67

Varijante proizvoda:

Broj pinova: 2-pin, 3-pin, 4-pin, 5-pin,
7-pin, 8-pin, 9-pin

Opis proizvoda:

Set industrijskih konektora vrhunske kvalitete s pozlaćenim kontaktima. Povećana otpornost na vibracije.

Zaštita: IP67

Maksimalni napon: 500V (2/3/4-pin), 250V (5/7/8/9-pin)

Maksimalni prijelazni napon: 2500V (2/3/4-pin), 1500V (5/7/8/9-pin)

Maksimalna struja: 10A (2/3/4-pin), 5A (5/7/8/9-pin)

Za promjere žice: 3-7 mm

Otpor izolacije: >500MΩ


Radna temperatura: -40 - 80°C

Promjer kontakta: 1,5 mm² (2/3/4-pin), 1,0 mm² (5/7/8/9-pin)

Materijal: plastika, metal, bakar

Sadržaj paketa: muški konektor, ženska utičnica

Galerija:



LP-16 - Datasheet

The number of pins	8P16	8P16	4P16	8P16	8P16	8P16	8P16
Rated current	16A	16A	16A	16A	16A	16A	16A
Rated voltage	600V	600V	600V	600V	600V	600V	600V
Rated frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated temperature	-30...+85°C	-30...+85°C	-30...+85°C	-30...+85°C	-30...+85°C	-30...+85°C	-30...+85°C
Dimensions	81.87x 111.87x 41.87	81.87x 111.87x 41.87	81.87x 111.87x 41.87	81.87x 111.87x 41.87	81.87x 111.87x 41.87	81.87x 111.87x 41.87	81.87x 111.87x 41.87
Weight	1.000g	1.000g	1.000g	1.000g	1.000g	1.000g	1.000g
Material	PC/ABS	PC/ABS	PC/ABS	PC/ABS	PC/ABS	PC/ABS	PC/ABS
Operating temperature	-30...+85°C	-30...+85°C	-30...+85°C	-30...+85°C	-30...+85°C	-30...+85°C	-30...+85°C
Storage temperature	-40...+125°C	-40...+125°C	-40...+125°C	-40...+125°C	-40...+125°C	-40...+125°C	-40...+125°C
Humidity	5% to 95% RH	5% to 95% RH	5% to 95% RH	5% to 95% RH	5% to 95% RH	5% to 95% RH	5% to 95% RH
Rated resistance	2000Ω	2000Ω	2000Ω	2000Ω	2000Ω	2000Ω	2000Ω
Shielding	Shielded	Shielded	Shielded	Shielded	Shielded	Shielded	Shielded
Operating voltage	0...600V AC/DC	0...600V AC/DC	0...600V AC/DC	0...600V AC/DC	0...600V AC/DC	0...600V AC/DC	0...600V AC/DC
Mounting	Panel	Panel	Panel	Panel	Panel	Panel	Panel
Material	PC/ABS	PC/ABS	PC/ABS	PC/ABS	PC/ABS	PC/ABS	PC/ABS
Conductor material	Copper with Ni-P and 0.5µm Gold plating	Copper with Ni-P and 0.5µm Gold plating	Copper with Ni-P and 0.5µm Gold plating	Copper with Ni-P and 0.5µm Gold plating	Copper with Ni-P and 0.5µm Gold plating	Copper with Ni-P and 0.5µm Gold plating	Copper with Ni-P and 0.5µm Gold plating

MATERIALS

Plastic parts: PC/ABS (UL94V-0)

Shielding: Shielded

Operating voltage: 0...600V AC/DC

Material: PC/ABS

Conductor material: Copper with Ni-P and 0.5µm Gold plating