

TY20 vijčani kabelski spojni konektor, IP68

Šifre proizvoda:

Šifra proizvoda: AM2930

EAN13: -

HS kód: 85369010

Parametri proizvoda:

Materijal kućišta: Plastični

Pokriti: IP68

Izgradnja: Uvrtnjem



Varijante proizvoda:

Broj pinova: 2-pin, 3-pin, 4-pin, 5-pin,
6-pin, 7-pin

Opis proizvoda:

Vodootporni docking konektor za žice promjera 6 - 11,5 mm. Dizajn vijaka.
Pozlaćeni kontakti.

Zaštita: IP68

Radna temperatura: -20 - 110°C

Relativna vlažnost: 90% - 95%

Materijal: poliamid

Paket sadrži mužjaka i ženku

Vrsta: TY20	2-pinski	3-pinski	4-pinski	5-pinski
Prosječni kontakti	2,8 mm	2,8 mm	2,8 mm	1,8 mm
Maks. Trenutno	25A	25A	25A	10A

Maks. Napetost	380V	380V	380V	380V
Kontaktni otpor	1mΩ	1mΩ	1mΩ	2 mΩ
Maks. presjek kabela	4 mm ²	4 mm ²	4 mm ²	1,5 mm ²

Galerija:



T120	02	03	04	05	06	07
Pin plug indicator front view						
Contact diameter (ØMM)	02,80	03,00	03,20	03,40	03,60	03,80
Panel diameter (Ø)	25,4	25,4	25,4	25,4	25,4	25,4
Operating Voltage (AC/DC)	380V	380V	380V	380V	380V	380V
Insulation resistance (MΩ)	10000	10000	10000	10000	10000	10000
Contact resistance (mΩ)	1	1	1	2	2	2
Insulation resistance (MΩ)	2000	2000	2000	2000	2000	2000
Cable specifications (mm ² /AWG)	4x1,0	4x1,2	4x1,5	4x1,5/14	4x1,5/14	4x1,5/14