

GX16, IP65 vodootporan konektor kabelaške veze, 4-pinski

Šifra proizvoda: AM6055
EAN13: -
HS kód: 85369010

Varijante proizvoda:

Parametri proizvoda:

Trenutno: 7 A
Napetost: 125 V AC
Pokriti: IP65
Broj pinova: 4-pin

Opis proizvoda:

Vodootporni docking konektor za žice promjera 4,5 - 7,1 mm.

Maksimalna struja: 7A

Maksimalni napon: 125V AC

Zaštita: IP65

Radna temperatura: -20 - 110°C

Relativna vlažnost: 90% - 95%

Materijal: poliamid



NO. OF CONTACTS	2	3	4	5	6	7	8	9	10
Rated current / voltage	7A-125V	7A-125V	7A-125V	5A-125V	4A-125V	4A-125V	4A-125V	4A-125V	4A-125V
Operation limit voltage (AC V.rms)	200	200	200	200	200	200	200	200	200
Withstanding voltage (AC V.rms) 1 minute	1500	1500	1500	1500	1500	1500	1500	1500	1500
Insulation resistance(MΩMIN.) at DC 500V	1500	1500	1500	1500	2000	2000	2000	2000	2000
Contact resistance (MΩ MAX.) AT DC 1A	10	10	10	10	10	10	10	10	10
Solder cup mouth aperture	1.5	1.5	1.5	1.2	0.8	0.8	0.8	0.8	0.8
Solder enter diameter	2.5	2.5	2.5	2	1.2	1.2	1.2	1.2	1.2



