

TY20 vijčani konektor kablanske ploče, IP68

Šifra proizvoda: AM3071

EAN13: -

HS kód: 85369010

Varijante proizvoda:

Broj pinova: 2-pin, 3-pin, 4-pin, 5-pin, 6-pin, 7-pin



Parametri proizvoda:

Materijal kućišta: Plastični

Pokriti: IP68

Izgradnja: Uvrtanjem

Opis proizvoda:

Vodootporni docking konektor za žice promjera 6 - 11,5 mm. Dizajn vijaka. Pozlaćeni kontakti.

Zaštita: IP68

Radna temperatura: -20 - 110°C

Relativna vlažnost: 90% - 95%

Materijal: poliamid

Paket sadrži mužjaka i ženku

Vrsta: TY20	2-pinski	3-pinski	4-pinski	5-pinski
Prosječni kontakti	2,8 mm	2,8 mm	2,8 mm	1,8 mm
Maks. Trenutno	25A	25A	25A	10A
Maks. Napetost	380V	380V	380V	380V
Maks. presjek kabela	4 mm ²	4 mm ²	4 mm ²	1,5 mm ²



	TY16	02	03	04		TY28	02	03	04
Pin plug insulator front view									
Contact diameter (φMM)	02.8X2	01.8X3	01X3			03.6X2	03.6X3	03.6X4	
Rated current (A)	16A	10A	5A			45A	45A	45A	
Operating Voltage (AC.V)	380V	380V	250V			380V	380V	380V	
Pressure resistance (AC.A)	1500V	1500V	1500V			1500V	1500V	1500V	
Contact resistance mΩ	1	2	5			0.5	0.5	0.5	
Insulation resistance MΩ	2000	2000	2000			2000	2000	2000	
Cable specifications (mm ² /AWG)	≤4/12	≤1.5/14	≤0.75/18			≤0/10	≤0/10	≤0/10	

	TY20	02	03	04	05	06	07
Pin plug insulator front view							
Contact diameter (φMM)	02.8X2	02.8X3	02.8X4	01.8X5	01X6	01X7	
Rated current (A)	25A	25A	25A	10A	5A	5A	
Operating Voltage (AC.V)	380V	380V	380V	380V	250V	250V	
Pressure resistance (AC.A)	1500V	1500V	1500V	1500V	1500V	1500V	
Contact resistance mΩ	1	1	1	2	5	5	
Insulation resistance MΩ	2000	2000	2000	2000	2000	2000	
Cable specifications (mm ² /AWG)	≤4/12	≤4/12	≤4/12	≤1.5/14	≤0.75/18	≤0.75/18	