

TY16 vijčani kabelski konektor, IP68

Šifre proizvoda:

Šifra proizvoda: AM7748

EAN13: -

HS kód: 85369010

Parametri proizvoda:

Materijal kućišta: Plastični

Pokriti: IP68

Izgradnja: Uvrtanjem



Varijante proizvoda:

Broj pinova: 2-pin, 3-pin, 4-pin

Opis proizvoda:

Vodootporni docking konektor za žice promjera 4,5 - 7,5 mm. Dizajn vijaka. Pozlaćeni kontakti.

Zaštita: IP68

Radna temperatura: -20 - 110°C

Relativna vlažnost: 90% - 95%

Materijal: poliamid

Paket sadrži mužjaka i ženku

Tip: TY16	2-pinski	3-pinski	4-pinski
Prosječni kontakti	2,8 mm	1,8 mm	1 mm
Maks. Trenutno	16A	10A	5A
Maks. Napetost	380V	380V	250V
Kontaktni otpor	1mΩ	2 mΩ	5mΩ
Maks. presjek	2	1,5 mm ²	0,75 mm ²

kabela

Galerija:



TY16	02	03	04
Pin plug insulator front view			
Contact diameter (MM)	Ø2.8X2	Ø1.8X3	Ø1X3
Rated current (A)	16A	10A	5A
Operating Voltage (ACV)	380V	380V	250V
Pressure resistance (ACV)	1500V	1500V	1500V
Contact resistance mΩ	1	2	5
Insulation resistance MΩ	2000	2000	2000
Cable specifications [mm ² /AWG]	4/12	1.5/14	0.75/18