

# Fusibile termico a saldare RY Tf 250V 15A

## Codici prodotto:

Riferimento: AM6313

EAN13: -

UPC: 85361000

## Caratteristiche del prodotto:

Attuale: 15 A

Tensione: 250 V AC

Tipo di fusibile: Veloce

Materiale dell'alloggiamento: Alluminio

Versione: Assiale



## Caratteristiche del prodotto:

Temperatura di azione: 73 °C, 75 °C, 80 °C, 95 °C, 100 °C, 105 °C, 113 °C, 110 °C, 115 °C, 120 °C, 121 °C, 125 °C, 130 °C, 133 °C, 135 °C, 140 °C, 142 °C, 145 °C, 150 °C, 152 °C, 155 °C, 157 °C, 165 °C, 167 °C, 172 °C, 175 °C, 185 °C, 192 °C, 195 °C, 200 °C, 205 °C, 210 °C, 216 °C, 240 °C, 250 °C, 255 °C, 280 °C

## Descrizione del prodotto:

Fusibile termico a saldare

Tensione nominale 250V AC

Corrente di picco massima: 15 A


Dimensioni: 4,2x12 mm

## Galleria del prodotto:

---



**Before action**



At normal operating temperatures, the current is routed from one end through the metal casing, the contact, to the other end of the lead (contact lead), making the circuit unblocked (and vice versa).

**After action**



When the device is in normal working condition, the temperature sensor is melted due to the temperature rise, and the temperature sensor is melted, the spring is automatically released, and the contact piece moves under the action of the spring, causing the contact piece and the contact line. Disconnected, the circuit is cut off.

