

Fusibile termico a saldare RY Tf 250V 15A

Codici prodotto:

Riferimento: AM6313

EAN13: -

UPC: 85361000

Caratteristiche del prodotto:

Attuale: 15 A

Tensione: 250 V AC

Tipo di fusibile: Veloce

Materiale dell'alloggiamento: Alluminio

Versione: Assiale



Caratteristiche del prodotto:

Temperatura di azione: 73 °C, 75 °C, 80 °C, 95 °C, 100 °C, 105 °C, 113 °C, 110 °C, 115 °C, 120 °C, 121 °C, 125 °C, 130 °C, 133 °C, 135 °C, 140 °C, 142 °C, 145 °C, 150 °C, 152 °C, 155 °C, 157 °C, 165 °C, 167 °C, 172 °C, 175 °C, 185 °C, 192 °C, 195 °C, 200 °C, 205 °C, 210 °C, 216 °C, 240 °C, 250 °C, 255 °C, 280 °C

Descrizione del prodotto:

Fusibile termico a saldare

Tensione nominale 250V AC


Corrente di picco massima: 15 A

Dimensioni: 4,2x12 mm

Galleria del prodotto:



Before action



At normal operating temperatures, the current is routed from one end through the metal casing, the contact, to the other end of the lead (contact lead), making the circuit unblocked (and vice versa).

After action



When the device is in normal working condition, the temperature sensor is melted due to the temperature rise, and the temperature sensor is melted, the spring is automatically released, and the contact piece moves under the action of the spring, causing the contact piece and the contact line. Disconnected, the circuit is cut off.

