

# TY20 conector de cablu de panou cu șurub, IP68

Referință: AM3071  
 EAN13: -  
 UPC: 85369010

## Atributele produsului:

Numărul de pini: 2-pin, 3-pin, 4-pin, 5-pin, 6-pin, 7-pin

## Caracteristicile produsului:

Materialul carcasei: Plastic  
 Acoperi: IP68  
 Construcție: Prin înșurubare



## Descriere produs:

Conector de andocare rezistent la apă pentru cabluri cu diametrul de 6 - 11,5 mm. Design cu șurub. Contacte placate cu aur.

Protecție:

IP68 Temperatura de

funcționare

: -20 - 110°C

Umiditate

relativă

: 90% - 95% Material

: Poliamidă

Pachetul include un bărbat și o femeie

Tip: TY20	2 pini	3-pini	4-pini	5 pini
Diametrul contactelor	2.8mm	2.8mm	2.8mm	1.8mm
Curent max.	25A	25A	25A	10A
Tensiune maximă.	380V	380V	380V	380V
Secțiunea maximă a cablului	4mm <sup>2</sup>	4mm <sup>2</sup>	4mm <sup>2</sup>	1.5mm <sup>2</sup>



TY16				TY28			
02	03	04		02	03	04	
Pin plug insulator front view				Pin plug insulator front view			
Contact diameter (φMM)	02.8X2	01.8X3	01X3	Contact diameter (φMM)	03.6x2	03.6x3	03.6x4
Rated current (A)	16A	10A	5A	Rated current (A)	45A	45A	45A
Operating Voltage (AC.V)	380V	380V	150V	Operating Voltage (AC.V)	380V	380V	380V
Pressure resistance (AC.A)	1500V	1500V	1500V	Pressure resistance (AC.A)	1900V	1500V	1500V
Contact resistance mΩ	1	2	5	Contact resistance mΩ	0.5	0.5	0.5
Insulation resistance MΩ	2000	2000	2000	Insulation resistance MΩ	2000	2000	2000
Cable specifications (mm <sup>2</sup> /AWG)	≤4/12	≤1.5/14	≤0.75/18	Cable specifications (mm <sup>2</sup> /AWG)	≤6/10	≤6/10	≤6/10

TY20						
02	03	04	05	06	07	
Pin plug insulator front view						
Contact diameter (φMM)	02.8X2	02.8X3	02.8X4	01.8X5	01X6	01X7
Rated current (A)	25A	25A	25A	10A	5A	5A
Operating Voltage (AC.V)	380V	380V	380V	380V	250V	250V
Pressure resistance (AC.A)	1500V	1500V	1500V	1500V	1500V	1500V
Contact resistance mΩ	1	1	1	2	5	5
Insulation resistance MΩ	2000	2000	2000	2000	2000	2000
Cable specifications (mm <sup>2</sup> /AWG)	≤4/12	≤4/12	≤4/12	≤1.5/14	≤0.75/18	≤0.75/18