

# Siguranță termică de lipit RY Tf 250V 15A

## coduri de produs:

Referință: AM6313

EAN13: -

UPC: 85361000

## Caracteristicile produsului:

Actual: 15 A

Tensiune: 250 V AC

Tipul siguranței: Rapid

Materialul carcasei: Aluminiu

Execuție: Axial



## Atributele produsului:

Temperatura de acțiune: 73 °C, 75 °C,  
80 °C, 95 °C, 100 °C, 105 °C, 113 °C,  
110 °C, 115 °C, 120 °C, 121 °C, 125 °C,  
130 °C, 133 °C, 135 °C, 140 °C, 142 °C,  
145 °C, 150 °C, 152 °C, 155 °C, 157 °C,  
165 °C, 167 °C, 172 °C, 175 °C, 185 °C,  
192 °C, 195 °C, 200 °C, 205 °C, 210 °C,  
216 °C, 240 °C, 250 °C, 255 °C, 280 °C

## Descriere produs:

Lipire cu siguranță termică

Tensiune nominală 250V AC

Curent maxim de vârf: 15 A


Dimensiune: 4.2x12mm

## Galerie de produse:

---



**Before action**



At normal operating temperatures, the current is routed from one end through the metal casing, the contact, to the other end of the lead (contact lead), making the circuit unblocked (and vice versa).

**After action**



When the device is in normal working condition, the temperature sensor is melted due to the temperature rise, and the temperature sensor is melted, the spring is automatically released, and the contact piece moves under the action of the spring, causing the contact piece and the contact line. Disconnected, the circuit is cut off.

