

TY20 vijačni panelni kabelski priključek, IP68

Koda izdelka: AM3071
EAN13: -
HS kód: 85369010

Variante izdelkov:

Število zatičev: 2-pin, 3-pin, 4-pin, 5-pin, 6-pin, 7-pin

Parametri izdelka:

Material ohišja: Plastika
Pokritost: IP68
Namestitev: Z vijačenjem

Opis izdelka:

Vodoodporen priklonni priključek za žice premera 6-11,5 mm. Zasnova z vijaki. Pozlačeni kontakti.

Zaščita IP68.

Delovna temperatura: -20 - 110 °C

Relativna vlažnost: 90 % - 95 %

Material: Poliamid

Paket vključuje moškega in ženske



Tip: TY20	2-pin	3-pinski priključek	4-pinski priključek	5-pinski priključek
Premjer stikov	2,8 mm	2,8 mm	2,8 mm	1,8 mm
Največji tok	25A	25A	25A	10A
Največja napetost	380V	380V	380V	380V
Največji prečni prerez kabla	4 mm2	4 mm2	4 mm2	1,5 mm2



TY16	02	03	04
Pin plug insulator front view			
Contact diameter (φMM)	Ø2.8X2	Ø1.8X3	Ø1X3
Rated current (A)	16A	10A	5A
Operating Voltage (AC.V)	380V	380V	250V
Pressure resistance (ACA)	1500V	1500V	1500V
Contact resistance mΩ	1	2	5
Insulation resistance MQ	2000	2000	2000
Cable specifications (mm²/AWG)	≤4/12	≤1.5/14	≤0.75/18

TY28	02	03	04
Pin plug insulator front view			
Contact diameter (φMM)	Ø3.6x2	Ø3.6x3	Ø3.6x4
Rated current (A)	45A	45A	45A
Operating Voltage (AC.V)	380V	380V	380V
Pressure resistance (ACA)	1500V	1500V	1500V
Contact resistance mΩ	0.5	0.5	0.5
Insulation resistance MQ	2000	2000	2000
Cable specifications (mm²/AWG)	≤6/10	≤6/10	≤6/10

TY20	02	03	04	05	06	07
Pin plug insulator front view						
Contact diameter (φMM)	Ø2.8X2	Ø2.8X3	Ø2.8X4	Ø1.8X5	Ø1X6	Ø1X7
Rated current (A)	25A	25A	25A	10A	5A	5A
Operating Voltage (AC.V)	380V	380V	380V	380V	250V	250V
Pressure resistance (ACA)	1500V	1500V	1500V	1500V	1500V	1500V
Contact resistance mΩ	1	1	1	2	5	5
Insulation resistance MQ	2000	2000	2000	2000	2000	2000
Cable specifications (mm²/AWG)	≤4/12	≤4/12	≤4/12	≤1.5/14	≤0.75/18	≤0.75/18