



odpor	≤6.15				≤2.54		≤0.78			
Max. p	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>	mm <sup>2</sup>
rierez										
vodiča										

Maximálny prúd: 25A

Maximálne napätie: 250V AC

Krytie: IP68

Pracovná teplota: -20 - 110 °C

Relatívna vlhkosť: 90% - 95%

Materiál: Polyamid

Obsah balenia: samec + samica SP20

### Galerie:



Max. current	25	25	25	25	25	25	25	25	25	25
Max. voltage	250	250	250	250	250	250	250	250	250	250
Max. temp.	-20	-20	-20	-20	-20	-20	-20	-20	-20	-20
Max. humidity	90	90	90	90	90	90	90	90	90	90
Max. temp. range	-20	-20	-20	-20	-20	-20	-20	-20	-20	-20
Max. humidity range	90	90	90	90	90	90	90	90	90	90
Max. temp. range	-20	-20	-20	-20	-20	-20	-20	-20	-20	-20
Max. humidity range	90	90	90	90	90	90	90	90	90	90
Max. temp. range	-20	-20	-20	-20	-20	-20	-20	-20	-20	-20
Max. humidity range	90	90	90	90	90	90	90	90	90	90