

SP16, IP68 vodeodolný káblový spojovací konektor

Kód produktu: AM3298
 EAN13: -
 HS kód: 85369010

Varianty produktu:

Počet pinov: 2-pin, 3-pin, 4-pin, 5-pin, 6-pin, 7-pin, 9-pin



Parametry produktu:

Materiál puzdra: Plast
 Krytie: IP68
 Inštalácia: Spájkovaním

Popis produktu:

Vodeodolný dokovacia konektor pre vodiče s priemerom 5.5 - 8mm. Pozlátené kontakty.

| Typ: SP16 | 2-pin | 3-pin | 4-pin | 5-pin | 7-pin | 9-pin |
|------------------|--------|--------|--------|--------|--------|--------|
| Priemer | 1.8mm | 1.8mm | 1mm | 1mm | 1mm | 1mm |
| kontaktov | | | | | | |
| Menovitý prúd | 10A | 5A | 5A | 5A | 5A | 5A |
| Menovité napätie | 250V | 250V | 250V | 250V | 250V | 250V |
| Odpor kontaktov | 2mΩ | 2mΩ | 5mΩ | 5mΩ | 5mΩ | 5mΩ |
| Izolačný odpor | 2000mΩ | 2000mΩ | 2000mΩ | 2000mΩ | 2000mΩ | 2000mΩ |

Maximálny prúd: 10A

Maximálne napätie: 250V AC

Krytie: IP68

Pracovná teplota: -20 - 110 °C

Relatívna vlhkosť: 90% - 95%

Materiál: Polyamid



| SP16 | 02 | 03 | 04 | 05 | 07 | 09 |
|----------------------------|--------|--------|-------|-------|-------|-------|
| Contact diameter | Ø1.8×2 | Ø1.8×3 | Ø1×4 | Ø1×5 | Ø1×7 | Ø1×9 |
| Rated current (A) | 10A | 5A | 5A | 5A | 5A | 5A |
| Rated voltage (AC, V) | 250V | 250V | 250V | 250V | 250V | 250V |
| Test voltage (AC, V) | 1500V | 1500V | 1500V | 1500V | 1500V | 1500V |
| Contact resistance (mΩ) | 2 | 2 | 5 | 5 | 5 | 5 |
| Insulation resistance (MΩ) | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 |



