

SP28, vodoodporni konektor za kabelsko spajanje IP68

Oznake izdelkov:

Koda izdelka: AM6945

EAN13: -

HS kód: 85369010

Parametri izdelka:

Material ohišja: Plastika

Pokritost: IP68



Variante izdelkov:

Število zatičev: 2-pin, 3-pin, 4-pin, 5-pin, 6-pin, 7-pin, 9-pin, 10-pin, 12-pin, 14-pin, 16-pin, 19-pin, 22-pin, 24-pin, 26-pin

Opis izdelka:

Vodoodporni priklopni konektor za žice s premerom 11 - 15 mm. Pozlačeni kontakti.

Premer stika			
Nazivni tok			
Nazivna napetost			

Kontakt	0,5 mΩ	0,5 mΩ	0,5 mΩ	1 mΩ	1 mΩ	1 mΩ	2 mΩ	2 mΩ	2 mΩ	2 mΩ	2 mΩ	5 mΩ	5 mΩ	5 mΩ	5 mΩ
Upornost	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω
Izolacijska upornost	≤10,1	≤10,1	≤10,1	≤6,15	≤6,15	≤6,15	≤2,	≤2,	≤2,	≤2,	≤2,	≤0,78	≤0,78	≤0,78	≤0,78
Maksimalni preseki vodnika	7 mm ²	7 mm ²	7 mm ²	2 mm ²	2 mm ²	2 mm ²	54 mm ²	54 mm ²	54 mm ²	54 mm ²	54 mm ²	mm ²	mm ²	mm ²	mm ²

Največja napetost: 250 V AC


Zaščita: IP68

Delovna temperatura: -20 - 110°C

Relativna vlažnost: 90 % - 95 %

Material: Poliamid

Galerija:



Model	PG19	PG7	PG9	PG13	PG16
Male contact	PG19	PG7	PG9	PG13	PG16
Female contact	PG19	PG7	PG9	PG13	PG16
Contact diameter	19,15	7,0	9,0	13,0	16,0
Rated current(I _N)	20A	10A	10A	20A	20A
Rated voltage(U _N)	250V	250V	250V	250V	250V
Insulation resistance	≥10 ⁹ Ω	≥10 ⁹ Ω	≥10 ⁹ Ω	≥10 ⁹ Ω	≥10 ⁹ Ω
Dielectric strength	≥10 ⁴ V/mm	≥10 ⁴ V/mm	≥10 ⁴ V/mm	≥10 ⁴ V/mm	≥10 ⁴ V/mm
Temperature resistance	-20...110 °C	-20...110 °C	-20...110 °C	-20...110 °C	-20...110 °C
Copper wire equivalent	2,0	2,0	2,0	2,0	2,0