

# Industriell kontakt LP-16, hane + hona (fyrkantigt uttag)

## Produktkoder:

Produktkod: AM8116

EAN13: -

HS-kod: 85369010



## Produktparametrar:

Täckning: IP67

## Produktvarianter:

Antal stift: 2-pin, 3-pin, 4-pin, 5-pin,  
7-pin, 8-pin, 9-pin

## Produktbeskrivning:

Högkvalitativa industriella kontaktsatser med guldpläterade kontakter.  
Ökad vibrationsbeständighet.

Skyddsklass: IP67

Maximal spänning: 500V (2/3/4-stift), 250V (5/7/8/9-stift)

Maximal tillfällig spänning: 2500V (2/3/4-stift), 1500V (5/7/8/9-stift)

Maximal ström: 10A (2/3/4-stift), 5A (5/7/8/9-stift)

För ledardiametrar: 3-7 mm.

Isoleringsmotstånd: >500MΩ

Driftstemperatur: -40 - 80 °C


Kontaktdiameter: 1,5 mm<sup>2</sup> (2/3/4-stift), 1,0 mm<sup>2</sup> (5/7/8/9-stift)

---

Material: plast, metall, koppar

Paketets innehåll: manlig kontakt, kvinnligt uttag

**Galerie:**



LP-16 - Datasheet

The number of pins	8P16	8P16	4P16	8P16	8P16	8P16	8P16
Pin configuration							
Rated current	16A	16A	16A	16A	16A	16A	16A
Rated voltage	600V	600V	600V	600V	600V	600V	600V
Rated power	9.6kW	9.6kW	9.6kW	9.6kW	9.6kW	9.6kW	9.6kW
Rated resistance	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Temperature class	165 °C	165 °C	165 °C	165 °C	165 °C	165 °C	165 °C
Dimensions	81.072	81.072	81.072	81.072	81.072	81.072	81.072
Weight	1.000g	1.000g	1.000g	1.000g	1.000g	1.000g	1.000g
Material	PA66	PA66	PA66	PA66	PA66	PA66	PA66
RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS compliance	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS exemption	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS category	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS code	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS description	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS reference	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS status	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS version	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS date	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer code	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer name	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer address	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer phone	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer fax	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer email	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer website	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer contact person	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer contact phone	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer contact fax	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer contact email	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS
RoHS manufacturer contact website	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS	RoHS

**MATERIALS**

Material: PA66 (Polyamide 66) - High performance engineering plastic  
 Pin: Brass (Copper alloy) - High conductivity  
 Contact: Brass (Copper alloy) - High conductivity  
 Insulation: PA66 (Polyamide 66) - High performance engineering plastic  
 Connector: PA66 (Polyamide 66) - High performance engineering plastic  
 Connector cover: PA66 (Polyamide 66) - High performance engineering plastic  
 Connector cap: PA66 (Polyamide 66) - High performance engineering plastic