

akt motstånd	mΩ	mΩ	mΩ													
Isole ring smotstånd	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200	200
Max. ledararea	≤10,1	≤10,1	≤10,1	≤6,15	≤6,15	≤6,15	≤2,54	≤2,54	≤2,54	≤2,54	≤2,54	≤0,78	≤0,78	≤0,78	≤0,78	
	7 mm ²	7 mm ²	7 mm ²	mm ²	mm ²	mm ²	54 mm ²	mm ²	54 mm ²	54 mm ²	mm ²	mm ²	mm ²	mm ²	mm ²	

Maximal spänning: 250V AC


Skydd: IP68

Arbetstemperatur: -20 - 110°C

Relativ luftfuktighet: 90 % - 95 %

Material: Polyamid

Galerie:



E12		E16		E20		E25		E31		E36	
Multi contact	2	3	4	5	6	7	8	9	10	11	12
Max. voltage	250V	250V	250V	250V	250V	250V	250V	250V	250V	250V	250V
Contact diameter	3,00	3,00	3,00	3,00	3,00	3,00	3,00	3,00	3,00	3,00	3,00
Rated current (AC)	10A	10A	10A	10A	10A	10A	10A	10A	10A	10A	10A
Rated voltage (AC)	250V	250V	250V	250V	250V	250V	250V	250V	250V	250V	250V
Test voltage (AC)	500V	500V	500V	500V	500V	500V	500V	500V	500V	500V	500V
Insulation resistance (DC)	100	100	100	100	100	100	100	100	100	100	100
Dielectric strength (AC)	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
Temperature resistance (°C)	-20/110	-20/110	-20/110	-20/110	-20/110	-20/110	-20/110	-20/110	-20/110	-20/110	-20/110